

/ Descriptions

SOT-89 PNP Silicon PNP transistor in a SOT-89 Plastic Package.


/ Features

Complements the 2SC4672,
Low saturation voltage, excellent DC current gain characteristics, complements the 2SC4672.


/ Applications

Power amplifier.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ Marking


h_{FE} Classifications Symbol	P	Q
h_{FE} Range	82 180	120 270
Marking	HAGP	HAGQ

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-50	V
Collector to Emitter Voltage	V_{CEO}	-50	V
Emitter to Base Voltage	V_{EBO}	-6.0	V
Collector Current-Continuous	I_C	-3.0	A
Collector Current -Continuous(Pulse)	I_{CP}	-6.0	A
Collector Power Dissipation	P_C	0.5	W
Collector Power Dissipation*	$*P_C$	2.0	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

*When mounted on a 40×40×0.7mm ceramic board.

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C = -50\mu A$	-50			V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C = -1.0mA$	-50			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E = -50\mu A$	-6.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = -50V$			-0.1	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB} = -5.0V$			-0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = -2.0V$ $I_C = -500mA$	82		270	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -1.0A$ $I_B = -50mA$		-0.15	-0.35	V


/ Electrical Characteristic Curve




/ Package Dimensions

SQT-89

单位: mm



/ Marking Instructions



H

AG

P: h_{FE}

**

Note:


H: Company Code.

AG: Product Type.

P: h_{FE} Classifications Symbol

**: Lot No. Code, code change with Lot No.

() / Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0luhh,



Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392

/ Notices