


TO-220F NPN Silicon NPN transistor in a TO-220F Plastic Package.

High DC current gain, low $V_{CE(sat)}$, large collector power dissipation, wide SOA.

Low frequency power amplifier.




PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	80	V
Collector to Emitter Voltage	V_{CEO}	60	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current - Continuous	I_C	3.0	A
Collector Current – Continuous(Pulse)	I_{CP}	6.0	A
Collector Power Dissipation	P_C	2.0	W
	$P_C(T_c=25^\circ\text{C})$	30	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=50\text{ }\mu\text{A}$	80			V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=1.0\text{mA}$	60			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=50\text{ }\mu\text{A}$	6.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=80\text{V}$ $I_E=0$			100	A
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=6.0\text{V}$ I_C				


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

D2396

H: h_{FE}

Note:


BR: Company Code.

D2396: Product Type.

H: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



- | | | | | |
|---|-------|-----|-----------|--------|
| 1 | 25 | 150 | 60 | 90sec; |
| 2 | 255±5 | | 5±0.5sec; | |
| 3 | | 2 | 10 | /sec. |

- Note:
- 1.Preheating:25~150 , Time:60~90sec.
 - 2.Peak Temp.:255±5 , Duration:5±0.5sec.
 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270±5	10±1 sec.	Temp.:270±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ Packaging SPEC.

/ BULK

Package Type	Units	Dimension	(unit mm ³)
--------------	-------	-----------	-------------------------