

/ Descriptions

TO-220F

Voltage Regulator in a TO-220F Plastic Package.

/ Features


1.5A,

3-Terminal regulators ,output current up to 1.5A, internal thermal overload protection and short-circuit limiting.


/ Applications

Voltage Regulator.

/ / Equivalent Circuit or Application Circuit



/ Pinning



PIN1 IN

PIN 2 GND

PIN 3 OUT


/ Marking

See Marking Instructions.


Parameter	Symbol	Rating	Unit
Input voltage	V_I	35	V
Thermal Resistance Junction-ambient	$R_{\theta JA}$	60	/W
Thermal Resistance Junction-case	$R_{\theta JC}$	5.0	/W
Operating Temperature Range	T_{OPR}	-40 125	
Storage temperature range	T_{stg}	-65 150	

Parameter			Conditions	Min	Typ	Max	Unit
Output voltage				14.4	15	15.6	V
			V 0A	14.25	15	15.75	V
Load Regulation			5A			300	mV
	Vo	Tj=25 Io=250mA-750mA				150	mV
Line regulation	Vo	Tj=25 Vi=17.5V-30V				300	mV
		Tj=25 Vi=20V-26V				150	mV
						8.0	mA
						1.0	mA
						0.5	mA
					-1.0		mV/
					90		μV/Vo
							dB
Dropout Voltage	Vd	Io=1A Tj=25			2.0		V
Output Resistance	Ro	f=1.0KHz			19		mΩ

/ Electrical Characteristic Curve




/ Package Dimensions



Symbol	Dimensions in Millimeters		Symbol	Dimensions in Millimeters	
	Min	Max		Min	Max
C	4.3	4.7	b1	2.9	3.9
A	9.7	10.3	a	0.55	0.75
B	14.7	15.3	E	2.29	2.79
B1	3.8	4.0	E1	2.29	2.79
R2	2.9	3.1	C1	2.5	2.8
R	3.0	3.4	C2	2.5	2.7
b	12.5	13.5	c	0.5	0.7

/ Marking Instructions



Note:

BR: Company Code

7815F: Product Type

****: Lot No. Code, code change with Lot No

() / Temperature Profile for Dip Soldering(Pb-Free)

Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 , Time:60~90sec.
- 2

255 5

5 0.5sec;

2.Peak Temp.:255 5 , Duration:5 0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270 5

10 1 sec.

Temp.:270±5

Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension					(unit mm ³)	
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	len	ll	ll	ll	ell	unit