

“Y / Descriptions

Silicon NPN transistor in a SOT-89 Plastic Package.


• È / Features

High current, Low saturation voltage.


v / Applications

Driver stages of audio and video amplifiers.

л ~ α = / Equivalent Circuit



ã | ũ / Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

т. н џ / Marking

$h_{FE(1)}$ Classifications	10	16
$h_{FE(1)}$ Range	63~160	100~250
Marking	HBC * *	HBD * *

绝对最大额定值 (Ta=25℃)



Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	45	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5	V
Collector Current-Continuous	I_C	1.0	A
Peak Collector Current	I_{CM}	1.5	A
Peak Base Current	I_{BM}	0.2	A
Collector Power Dissipation	P_C	0.5	W
	$*P_C$	1.3	W
Storage Temperature Range	T_{stg}	-55~150	

*:Device mounted on a printed-circuit board, single side copper, mounting pad for collector 6cm².

电 气 特 性 (Ta=25℃)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	$I_{CBO(1)}$	$V_{Cb}=30V$ $I_E=0$			0.1	μA
	$I_{CBO(2)}$	$V_{Cb}=30V$ $I_E=0$ $T_J=125$			10	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB}=5V$ $I_C=0$			0.1	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=2V$ $I_C=150mA$	63		250	
	$h_{FE(2)}$	$V_{CE}=2V$ $I_C=5mA$	63			
	$h_{FE(3)}$	$V_{CE}=2V$ $I_C=500mA$	40			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=500mA$ $I_B=50mA$			0.5	V
Base to Emitter Voltage	V_{BE}	$I_C=500mA$ $V_{CE}=2V$			1	V
Transition Frequency	f_T	$I_C=10mA$ $V_{CE}=5V$ $f=100MHz$		130		MHz
DC Current Gain Ratio Of The Complementary Pairs	$\frac{h_{FE1}}{h_{FE2}}$	$ I_C =150mA$ $ V_{CE} =2V$		1.3	1.6	


Electrical Characteristic Curve




⊂ É Ò Ì f / Package Dimensions

SOT-89

单位: mm



1. 标记 / Marking Instructions



H
BC

Note:


H: Company Code.

BC: Product Type.

** : Lot No. Code, code change with Lot No.



Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0lueh,



Note:

1. Preheating: 25~150 , Time: 60~90sec.
2. Peak Temp.: 245 ± 5 , Duration: 5 ± 0.5sec.
3. Cooling Speed: 2~10 /sec.

Resistance to Soldering Heat Test Conditions

260 ± 5 10 ± 1 sec. Temp.: 260±5 Time: 10±1 sec

Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7" x12	180×120×180	385×257×392

Notices