


Silicon NPN transistor in a TO-18 Plastic Package.

Complementary pair with BD439.

Medium power linear and switching applications.





PIN1	Emitter	PIN 2	Collector	PIN 3	Base
------	---------	-------	-----------	-------	------

See Marking Instructions.


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	45	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	4.0	A
Base Current - Continuous	I_B	0.1	A
Collector Power Dissipation	P_C	40	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=50mA$ $I_B=0$	45			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=\text{Rated } BV_{CEO}$ $I_E=0$			0.2	mA
Collector Cut-Off Current	I_{CEO}	$V_{CE}=\text{Half Rated } V_{CEO}$ $I_B=0$			500	μA
Emitter Cut-Off Current	I_{EBO}	$V_{BE}=5.0V$ $I_C=0$			2.0	mA
DC Current Gain	h_{FE}	$V_{CE}=3.0V$ $I_C=1.5A$	750			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=2.0A$ $I_B=40mA$			2.8	V
Base to Emitter On Voltage	$V_{BE(on)}$	$I_C=2.0A$ $V_{CE}=3.0V$			2.5	V




FW-126T

单位: mm



B	10,0	11,2	E	4,4	4,8
B1	3,8	4,2	C	3,1	3,3
a	1,27	1,27	C1	1,9	2,1
b	14	16	c	0,3	0,6
b1	1,9		a	1,27	
E1	2,1	2,5			




Note:

BR: Company Code

BD675: Product Type.

****: Lot No. Code, code change with Lot No.



Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 , Time:60~90sec.
- 2

255 5

5 0.5sec;

2.Peak Temp.:255 5 , Duration:5 0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

270 5

10 1 sec.

Temp.:270±5

Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱