

/ Descriptions


Silicon NPN transistor in a TO-92 Plastic Package.

/ Features

Low current, low voltage.

/ Applications

HF applications in radio and television receivers, FM tuners, low noise AM mixer-oscillators.

/ Equivalent Circuit**/ Pinning**

PIN1 Collector PIN 2 Emitter PIN 3 Base



/ hFE Classifications & Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	30	V
Collector to Emitter Voltage	V_{CEO}	20	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	30	mA
Peak Collector Current	I_{CM}	30	mA
Collector Power Dissipation	P_C	300	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=20V$ $I_E=0$			0.1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=4.0V$ $I_C=0$			0.04	μA
DC Current Gain	h					


/ Electrical Characteristic Curve




/ Package Dimensions

TO-92

Unit: mm



/ Marking Instructions




Note:

BR: Company Code.

BF494: Product Type.

****: Lot No. Code,code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



- Note:
- 1.Preheating:25~150 , Time:60~90sec.
 - 2.Peak Temp.:255 5 , Duration:5 0.5sec.
 - 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270 ± 5 10 ± 1 sec. Temp:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195