


LFPAK5×6 N
 N-Channel MOSFET in a LFPAK5×6 Plastic Package.

$V_{DS} (V) = 30V$ $I_D = 300A$
 $R_{DS(ON)}@10V$ 0.55mΩ(Typ. 0.48mΩ)
 $R_{DS(ON)}@4.5V$ 0.95mΩ(Typ. 0.82mΩ)
 HF Product.

DC-DC
 Motor drivers, DC - DC Converter.






PIN1 2 3 S PIN4 G Tab D


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	30	V
Drain Current	$I_D(T_c=25^\circ\text{C})$	300	A
	$I_D(T_c=100^\circ\text{C})$	300	A
Pulsed Drain Current	I_{DM}	1200	A
Gate-Source Voltage	V_{GS}	20	V
Single Pulsed Avalanche Energy $L=1.0\text{mH}$	E_{AS}	1624	mJ
Continuous-Source Current	I_S	300	A
Total Power Dissipation	$P_D(T_c=25^\circ\text{C})$	375	W
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 175	

Thermal Resist16 85(l Res)-8.7(i)-.7()Tj10.4962 591.68 .48 18.489.0117 Tw[1583.8203 Tmbie)7.12033 T(c0 Tw0


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Total Gate Charge	Q_g	$V_{GS}=10V, \quad V_{DS}=15V,$ $I_D=50A$		306		nC
Gate Source Charge	Q_{gs}			63		
Gate Drain Charge	Q_{gd}			44		
Turn-On Delay Time	$t_{d(on)}$	$V_{GEN}=10V \quad V_{DS}=15V$ $R_L=0.3\Omega \quad R_G=3.9\Omega$ $I_{DS}=50A$		23		ns
Turn-On Rise Time	t_r			151		
Turn-Off Delay Time	$t_{d(off)}$			249		
Turn-Off Fall Time	t_f			127		






7. Transfer Characteristics

8. Normalized Threshold Voltage





9. On-Resistance

10. Drain Current



11. Capacitance

12. Gate Charge



Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	MIN.	MAX.		MIN.	MAX.
A	1.00	1.30	E	4.95	5.30
A1	0.00	0.15	E1	3.50	3.70
A2	0.98	1.12	e	1.27 BSC.	
b	0.35	0.50	H	5.95	6.2
b1	0.32	0.46	i	-	0.2
b2	4.02	4.41	L	0.40	0.85
b3	4.00	4.37	L1	0.27	0.57
c	0.19	0.25	L2	0.80	1.30
c1	0.17	0.23	theta	0°	8°
c2	0.24	0.30			
c3	0.22	0.28			
D	4.45	4.70			
DI	-	4.45			



006N03S


Note

BR: Company Code

006N03S: Product Type Code

*****: Lot No. Code, code change with Lot No.

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245 5

5 0.5sec;

2.Peak Temp.:245 5 , Duration:5 0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
LFPK5×6	3,000	2	6,000	5	30,000	13"×12	356×335×50	385×285×358

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
LFPK5×6	5,000	2	10,000	5	50,000	13"×12	356×335×50	385×285×358

All information provided in this document is subject to legal disclaimers.