

BRCS009N10SHCD

Rev.A Jul.-2025



DATA SHEET

TO-263-7LA N

N-CHANNEL MOSFET in a TO-263-7LA Plastic Package.

BRCS009N10SHCD

Rev.A Jul.-2025



DATA SHEET

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V _{DSS}	100	V
Drain Current DC		I _D (T _C =25)	300	A
		I _D (T _C =100)	300	A
Pulsed Drain Current ^{*,**}		I _{DM}	1200	A
Gate-Source Voltage		V _{GS}	±20	V
Continuous-Source Current		I _S (T _C =25)	300	A
Single Pulsed Avalanche Energy L=1.0mH		E _{AS}	2592	mJ
Total Power Dissipation		P _D (T _C =25)	750	W
Junction and Storage Temperature Range		T _J ,T _{STG}	-55 to 175	
Thermal Resistance-Junction to Ambient ^{**}	Steady-State	R _{θJA}	44	/W
Thermal Resistance-Junction to Case ^{**}	Steady-State	R _{θJC}	0.2	

Notes:

* Pulse width 300 μs , duty cycle 2 %

** Surface Mounted on minimum footprint pad area


*** Limited by bonding wire

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------




/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Total Gate Charge	Q_g	$V_{GS}=10V$ $V_{DS}=50V$ $I_D=50A$		176		nC
Gate Source Charge	Q_{gs}			75		
Gate Drain Charge	Q_{gd}			32		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=1$ $R_{GEN}=3.9$ $I_{DS}=50A$		46		nS
Turn-On Rise Time	t_r			94		
Turn-Off Delay Time	$t_{d(off)}$			69		
Turn-Off Fall Time	t_f			70		


/ Electrical Characteristic Curve




Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

009N10SH


Note:

BR: Company Code

009N10SH: Product Type Code

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
TO-263-7LA	800	1	800	6	4,800	13 ×24	360×360×50	380×335×366

/ Notices

All information provided in this document is subject to legal disclaimers.