



Rev.A Feb.-2025

PDFN5×6A                      N  
 Dual N-CHANNEL MOSFET in a PDFN5×6A Plastic Package.

$V_{DS}(V)=30V$        $I_D=41.5A$   
 $R_{DS(ON)}@10V<9m\Omega$ (Typ. 6.8 m $\Omega$ )  
 $R_{DS(ON)}@4.5V<15m\Omega$ (Typ. 9.8 m $\Omega$ )  
 HF Product.

PWM                                      LED  
 PWM Application, Load Switch, Power Management, Dimming LED.



See Marking Instructions.

| Parameter                              | Symbol                               | Rating      | Unit |
|----------------------------------------|--------------------------------------|-------------|------|
| Drain-Source Voltage                   | $V_{DS}$                             | 30          | V    |
| Gate-Source Voltage                    | $V_{GS}$                             | $\pm 20$    | V    |
| Continuous Drain Current               | $I_D(T_C=25^\circ\text{C})$          | 41.5        | A    |
| Pulsed Drain Current                   | $I_{DM}$                             | 131         | A    |
| Power Dissipation                      | $P_D(T_C=25^\circ\text{C})$          | 25          | W    |
| Junction and Storage Temperature Range | $T_J, T_{STG}$                       | -55 to +150 |      |
| Maximum Junction-to-Ambient            | $R_{\theta JA}(10s)$                 | 45          | /W   |
| Maximum Junction-to-Ambient            | $R_{\theta JA}(\text{Steady-State})$ | 65          | /W   |
| Maximum Junction-to-Case               | $R_{\theta JC}(\text{Steady-State})$ | 5.0         | /W   |

| Parameter                         | Symbol        | Test Conditions                        | Min | Typ  | Max | Unit       |
|-----------------------------------|---------------|----------------------------------------|-----|------|-----|------------|
| Drain-Source Breakdown Voltage    | $BV_{DS}$     | $V_{GS}=0V$ $I_D=250\mu A$             | 30  | 36   |     | V          |
| Zero Gate Voltage Drain Current   | $I_{DSS}$     | $V_{DS}=30V$ $V_{GS}=0V$               |     |      | 1   | $\mu A$    |
| Gate-Body leakage current         | $I_{GSS}$     | $V_{GS}=\pm 20V$ $V_{DS}=0V$           |     |      | 100 | nA         |
| Gate Threshold Voltage            | $V_{GS(th)}$  | $V_{DS}=V_{GS}$ $I_D=250\mu A$         | 1.0 | 1.6  | 2.5 | V          |
| Static Drain-Source On-Resistance | $R_{DS(on)}$  | $V_{GS}=10V$ $I_D=10A$                 |     | 6.8  | 9   | m $\Omega$ |
|                                   |               | $V_{GS}=4.5V$ $I_D=10A$                |     | 9.8  | 15  | m $\Omega$ |
| Diode Forward Voltage             | $V_{SD}$      | $V_{GS}=0V$ $I_S=1.0A$                 |     |      | 1.2 | V          |
| Input Capacitance                 | $C_{iss}$     | $V_{DS}=25V$ $V_{GS}=0V$<br>$f=1.0MHz$ |     | 1100 |     | pF         |
| Output Capacitance                | $C_{oss}$     |                                        |     | 125  |     | pF         |
| Reverse Transfer Capacitance      | $C_{rss}$     |                                        |     | 100  |     | pF         |
| Gate resistance                   | $R_g$         | $V_{DS}=0V$ $V_{GS}=0V$<br>$f=1.0MHz$  |     | 3    |     | $\Omega$   |
| Total Gate Charge                 | $Q_{g(10V)}$  | $V_{GS}=10V$ $V_{DS}=15V$<br>$I_D=12A$ |     | 14   |     | nC         |
| Total Gate Charge                 | $Q_{g(4.5V)}$ |                                        |     | 6.5  |     | nC         |
| Gate-Source Charge                | $Q_{gs}$      |                                        |     | 2.3  |     | nC         |
| Gate-Drain Charge                 | $Q_{gd}$      |                                        |     | 3    |     | nC         |

| Parameter           | Symbol       | Test Conditions                                                                      | Min | Typ | Max | Unit |
|---------------------|--------------|--------------------------------------------------------------------------------------|-----|-----|-----|------|
| Turn-On Delay Time  | $t_{d(on)}$  | $V_{DS}=15\text{ V}$<br>$R_L=1.25\Omega$<br>$V_{GS}=10\text{V}$<br>$R_{GEN}=3\Omega$ |     | 4.5 |     | ns   |
| Turn-On Rise Time   | $t_r$        |                                                                                      |     | 10  |     | ns   |
| Turn-Off Delay Time | $t_{d(off)}$ |                                                                                      |     | 15  |     | ns   |

.004S3




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage









Figure 6: Body Diode Characteristics




PDFN5 X6A

Unit:mm



Rev.01 202209



BR

080N03

\*\*\*\*

Note

BR


Company Code

080N03

Product Type Code

\*\*\*\*:

Lot No. Code, code change with Lot No



- 1

150 180

60 90sec;

2

245±5

5±0.5sec;

3

2 10

/sec.
- Note:

1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

| Package Type | Units           |                      |                      |                            |                      | Dimension (unit mm <sup>3</sup> ) |            |             |
|--------------|-----------------|----------------------|----------------------|----------------------------|----------------------|-----------------------------------|------------|-------------|
|              | Units/Reel<br>/ | Reels/Inner Box<br>/ | Units/Inner Box<br>/ | Inner Boxes/Outer Box<br>/ | Units/Outer Box<br>/ | Reel                              | Inner Box  | Outer Box   |
| PDFN5×6A     | 5,000           | 2                    | 10,000               | 6                          | 60,000               | 13"×12                            | 360×360×50 | 380×335×366 |