

/ Descriptions

TO-252 N MOS N-CHANNEL MOSFET in a TO-252 Plastic Package.



/ Features

Low gate charge, low crss, fast switching. Halogen-free Product,HF Product.

/ Applications

DC/DC

These devices are well suited for high efficiency switching DC/DC converters and switch mode power supplies.


/ Equivalent Circuit**/ Pinning**

PIN1 G PIN 2 D PIN 3 S PIN 4 D


/ Marking

See Marking Instructions

/ Electrical Characteristic Curve



/ Marking Instructions



BR

7N65

Note:


BR: Company Code

7N65: Product Type

****: Lot No. Code, code change with Lot No

() /

7HPSHUDWXUH



7LPH VHF

Note:

- | | | | |
|---|---------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 7~E	Units ;>0 H					Dimension ;>0 p . (unit /mm ³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
TO-252	2,500	2	5,000	6	30,000	13s ×16	360×360×50	380×335×366

/ TUBE

Package Type 7~E	Units ;>0 H					Dimension ;>0 p . (unit /mm ³)		
	Units/Tube /•1×	Tubes/Inner Box •1× /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Tube•1×	Inner Box	Outer Boxç
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

/ Notices