

/ Descriptions

SOT-323

NPN



Silicon NPN Digital Transistor in a SOT-323 Plastic Package.

/ Features

With built-in bias resistors, simplify circuit design, reduce a quantity of parts and manufacturing process, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications

Switching, Inverter circuit, Interface circuit and driver circuit applications, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit**/ Pinning**





PIN1 Base PIN 2 Emitter PIN 3 Collector

/ hFE Classifications & Marking

Marking	Q24
---------	-----



/ Electrical Characteristic Curve







/ Package Dimensions

SOT-323

单位: mm



/ Marking Instructions




24

Note:

Q: Automobile halogen-free product Code

24 Product Type Code

() /



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255 5

5 0.5sec;

2.Peak Temp.:255 5 , Duration:5 0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices