

“Y

TO-252 ၁ Voltage Regulator in a TO-252 Plastic Package.

• È

' H , ၁ 800mA, ၂ ၁ DHF0T433


High efficiency, Low dropout voltage(1V TYP.)output current up to 800mA, internal current and thermal limit, Qualified to AEC-Q100 Standards for High Reliability, HF Product.

v


၁ ၂ ၃ [OBJ]

Voltage Regulator, Meet the stringent requirements of automotive applications.

၂ ၵ ၃ ၄



ၵ ၵ ၵ



PIN1 ၵ GND/ADJ

PIN 2,4 ၵ OUT

PIN 3 ၵ IN

၃. H ၵ

၁
See Marking Instructions.

电 压

J

Parameter	Symbol	Rating	Unit
Input voltage	V_I	15	V
Thermal Resistance Junction-case	$R_{\theta JC}$	8	/W
Storage temperature range	T_{stg}	-40 150	

参 数

J

Parameter	Symbol	Type	Test Conditions	Min	Typ	Max	Unit
Reference Voltage	V_{ref}	BRLD1117DQ- Adj	$V_{in}-V_o=2V \quad T_j=25$ $I_o=10mA$	1.225	1.25	1.275	V
			$10mA \leq I_o \leq 800mA$ $1.4V \leq (V_{in}-V_o) \leq 10V$	1.225	1.25	1.275	
Output Voltage	V_o	BRLD1117DQ-1.2	$V_{in}=3.2V \quad T_j=25$ $I_o=10mA$	1.176	1.2	1.224	V
			$10mA \leq I_o \leq 800mA$, $3V \leq V_{in} \leq 8V$	1.176	1.2	1.224	
		BRLD1117DQ-1.8	$V_{in}=3.8V \quad T_j=25$ $I_o=10mA$	1.764	1.8	1.836	V
			$0 \leq I_o \leq 800mA$, $3.3V \leq V_{in} \leq 8V$	1.764	1.8	1.836	
		BRLD1117DQ-2.5	$V_{in}=4.5V \quad T_j=25$ $I_o=10mA$	2.45	2.5	2.55	V
			$0 \leq I_o \leq 800mA$, $3.9V \leq V_{in} \leq 10V$	2.45	2.5	2.55	
		BRLD1117DQ-3.3	$V_{in}=5.3V \quad T_j=25$ $I_o=10mA$	3.234	3.3	3.366	V
			$0 \leq I_o \leq 800mA$, $4.75V \leq V_{in} \leq 10V$	3.234	3.3	3.366	
		BRLD1117DQ-5.0	$V_{in}=7V \quad T_j=25$ $I_o=10mA$	4.9	5	5.1	V
			$0 \leq I_o \leq 800mA$, $6.5V \leq V_{in} \leq 15V$	4.9	5	5.1	
Load Regulation	V_o	BRLD1117DQ-Adj	$V_{in}-V_o=3V$ $10mA \leq I_o \leq 800mA$			30	mV
		BRLD1117DQ-1.2	$V_{in}=3V$ $10mA \leq I_o \leq 800mA$			30	mV
		BRLD1117DQ-1.8	$V_{in}=3.3V$ $0mA \leq I_o \leq 800mA$			30	mV
		BRLD1117DQ-2.5	$V_{in}=3.9V$ $0mA \leq I_o \leq 800mA$			30	mV
		BRLD1117DQ-3.3	$V_{in}=4.75V$ $0mA \leq I_o \leq 800mA$			30	mV
		BRLD1117DQ-5.0	$V_{in}=6.5V$ $0mA \leq I_o \leq 800mA$			30	mV






13A

J


Parameter	Symbol	Type	Test Conditions	Min	Typ	Max	Unit
Line Regulation	Vo	BRLD1117DQ-Adj	Io=10mA 1.5V≤(Vin-Vo)≤13.75V			23	mV
		BRLD1117DQ-1.2	3V≤Vin≤8.0V Io=0mA			18	mV
		BRLD1117DQ-1.8	3.3V≤Vin≤8.0V Io=0mA			31	mV
		BRLD1117DQ-2.5	3.9V≤Vin≤10V Io=0mA			40	mV
		BRLD1117DQ-3.3	4.75V≤Vin≤15V Io=0mA			48	mV
		BRLD1117DQ-5.0	6.5V≤Vin≤15V Io=0mA			55	mV
Operating Input Voltage	Vin	BRLD1117DQ-Adj				15	V
		BRLD1117DQ-1.2	Io=100mA			10	
		BRLD1117DQ-1.8				10	
		BRLD1117DQ-2.5				15	
		BRLD1117DQ-3.3				15	
		BRLD1117DQ-5.0				15	
Adjustment Pin Current	Iadj	BRLD1117DQ-Adj	Vin≤15V		60	120	uA
Adjustment Pin Current Change	Iadj		1.4V≤Vin-Vo≤10V, 0mA≤Io≤800mA		1	5	
Quiescent Current	Id	BRLD1117DQ-1.2	Vin≤8V		5	10	mA
		BRLD1117DQ-1.8	Vin≤8V				
		BRLD1117DQ-2.5	Vin≤10V				
		BRLD1117DQ-3.3	Vin≤15V				
		BRLD1117DQ-5.0					
Output Current	Io	BRLD1117DQ-Adj	Vin-Vo=5V Tj=25	600	800	1000	mA
		BRLD1117DQ-1.2					
		BRLD1117DQ-1.8					
		BRLD1117DQ-2.5					
		BRLD1117DQ-3.3					
		BRLD1117DQ-5.0					
Output Noise	eN	BRLD1117DQ-Adj	10Hz≤B≤10KHz Tj=25		0.003	100	uV
		BRLD1117DQ-1.2					
		BRLD1117DQ-1.8					
		BRLD1117DQ-2.5					
		BRLD1117DQ-3.3					
		BRLD1117DQ-5.0					

Parameter	Symbol	Type	Test Conditions	Min	Typ	Max	Unit
Supply Voltage Rejection	SVR	BRLD1117DQ-Adj	$I_o=40\text{mA}$ $f=120\text{Hz}$, $T_j=25$ $V_{in}-V_o=3\text{V}$, $V_{ripple}=1\text{Vpp}$	60	75		dB
		BRLD1117DQ-1.2					
		BRLD1117DQ-1.8					

电 压 调 节 器

 $V_{DROP} - I_O$

 $V_O - T_a$

 $I_{ADJ} - T_a$

 $P_D - T_a$


1. 符号




	X	
EU	X	W
Q	X	
LG444 : G	X	N
45-		415V
****	X	I N I N

Note:

BR:	Company Code
Q:	Automobile halogen-free product Code
LD1117D:	Product Type Code
12:	On Behalf 1.2V
****:	Lot No. Code, code change with Lot No

Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0luhh,



- Note:
- 1. Preheating: 150~200 , Time: 60~120sec.
 - 2. Peak Temp.: 255±5 , Duration: 5±0.5sec.
 - 3. Cooling Speed: 2~10 /sec.

χ 260±5 χ 10±1 sec. Temp.: 260±5 Time: 10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
TO-252	2,500	2	5,000	6	30,000	13 ×16	360×360×50	380×335×366

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

ä v "Ω