

/ Descriptions

1.2A ABF
1.2A Surface Mount Glass Passivated Bridge Rectifier, ABF thin package.


/ Features

1000V 1.2A
Glass Passivated Chip Junction,Reverse Voltage: 1000V,Forward Current:1.2A, Fast reverse recovery time,Designed for Surface Mount Application.Halogen free product.


/ Applications

General purpose.

/ Equivalent Circuit




/ Pinning



PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)

~~The recommended mounting pad size~~



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Average Rectified Output Current at $T_c = 125$	I_o	1.2	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	40	A
Typical Junction Capacitance ^{Note1}	C_j	30	pF
Typical Thermal Resistance ^{Note2}	$R_{\theta JA}$	75	/W
Operating and Storage Temperature Range	T_j, T_{stg}	-55~150	


Note:

- 1.Measured at 1MHz and applied reverse voltage of 4 V D.C.
2. Mounted on glass epoxy PC board with 4 × 1.0" X 1.0" (2.54 X 2.54 cm) copper pad.

/ Electrical Characteristics(Ta=25)


Parameter	Symbol	Test Conditions	Rating	Unit
Forward Voltage per element	V_F	$I_F=1.2A$	1.3	V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I_R	$T_a=25$	5.0	μA
		$T_a=125$	50	μA
Maximum Reverse Recovery Time	t_{rr}	$I_F=0.5A$ $I_R=1.0A$ $I_{rr}=0.25A$	200	ns

/ Electrical Characteristic Curve




/ Package Dimensions

ABF




/ Marking Instructions

Marking

Type number	Marking code
FTB10F-12	F10F12
	

() /



Note:

- 1

25 150

60 90sec;
- 2

245 5

5 0.5sec;
- 3

2 10 /sec.
- 1.Preheating:25~150 , Time:60~90sec.

2.Peak Temp.:245 5 , Duration:5 0.5sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260 5 Time:10 1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
	5000	2	10000	5	50000	13 ×15	336X336X40	380X335X366

/ Notices