

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RM} V_{RSM} V_{DC}	100	V
RMS Reverse Voltage	V_{RMS}	70	V
Average forward rectified current	$I_{F(AV)}$	1×10	A
Non Repetitive Peak Surge Current	I_{FSM}	200	A
Typical Thermal Resistance ^{Note 1}	$R_{\theta JA}$	70	/W
	$R_{\theta JC}$	1.4	/W
Junction and Storage Temperature Range	T_j T_{stg}	-55 +150	

/ Electrical Characteristics(Ta=25)






Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	$V_{(BR)R}$	$I_R=1mA(Ta=25)$	100			V
Forward Voltage	V_F	$I_F=2A(Ta=25)$		0.41	0.45	V
		$I_F=10A(Ta=25)$		0.58	0.65	V
		$I_F=2A(Ta=125)$		0.31	0.40	V
		$I_F=10A(Ta=125)$		0.55	0.65	V
Instantaneous Reverse Current	I_R ^{Note 2}	$V_R=100V(Ta=25)$			150	μA
		$V_R=100V(Ta=125)$			25	mA

Polymide PCB, 2oz. Copper. Cathode pad dimensions 18.8mm x 14.4mm. Anode pad dimensions 5.6mm x 14.4mm.


Short duration pulse test used to minimize self-heating effect.

Unless otherwise noted, values for the parameters of a single chip.

/ Electrical Characteristic Curve




/ Package Dimensions





() /



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245 5

5 0.5sec;

2.Peak Temp.:245 5 , Duration:5 0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-277	5,000	3	15,000	6	90,000	13 ×12	360×360×50	380×335×366

/ Notices