

/ Descriptions

TO-220


/ Features

/ Applications


OR-ing

DC-DC

/ Equivalent Circuit



/ Pinning




/ h_{FE} Classifications & Marking

		x	
	θ		

--	--	--	--	--

/ Electrical Characteristic Curve




/ Package Dimensions

L : mm


TO-220

单位



Symbol	Dimensions in milimeters		Symbol	Dimensions in millimeters	
	Min	Max		Min	Max
A	9.8	10.2	C	12	14
B	3.56	3.64	B1	6.3	6.7
B2	9.0	9.4		15.7	16.1
C1	0.7	0.8		0.7	0.8
a	1.22	1.32		0.4	0.6
b1	0.2	0.25		0.25	0.45
k	0.2	0.25		0.25	0.45

/ Marking Instructions



() / Temperature Profile for Dip Soldering(Pb-Free)

 $\pm$ $\pm$ $\pm$ $\pm$

/ Resistance to Soldering Heat Test Conditions

 $\pm$ $\pm$

/ Packaging SPEC.

封装形式	包装数量					包装尺寸		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

封装形式	包装数量					包装尺寸		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices