

/ Descriptions

TO-220F


/ Features

/ Applications

OR-ing

DC-DC

/ Equivalent Circuit



/ Pinning



:

:

:

/ h_{FE} Classifications & Marking

/ Absolute Maximum Ratings(Ta=25)

		×	
	θ		
		~	


/ Electrical Characteristics(Ta=25)

	()					μ


/Notes

1.
2.

/ Electrical Characteristic Curve




/ Package Dimensions



Dimensions in Millimeters

Symbol	Min	Max	Symbol	Min	Max
C	4.3	4.7	b1	2.9	3.9
A	9.7	10.3	a	0.55	0.75
B	14.7	15.3	E	2.29	2.79
b1	2.9	4.0	E1	2.29	2.79
R2	2.9	3.1	C1	2.5	2.9
R	3.0	3.4	C2	2.5	2.7
b	12.5	13.5	c	0.5	0.7

/ Marking Instructions



BR

LV30Q100

CT:

F:

$\pm$ $\pm$

	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

6 6