

/ Descriptions

TO-3P



TO-3P Plastic package Schottky diode .

/ Features

Low forward voltage drop,low power losses,High efficiency operation.

/ Applications

For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications.

/ Equivalent Circuit**/ Pinning**

PIN1 Anode

PIN 2 Cathode






PIN 3 Anode

/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	500	V
Working Peak Reverse Voltage		10	V
DC Reverse Voltage		5	V


I Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

MBR2045PT


Note:

BR: Company Code

MBR2045PT: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

255±5

5±0.5sec;
- 3

2 10 /sec.
- 1.Preheating:25~150 , Time:60~90sec.

2.Peak Temp.:255±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5℃ Time:10±1 sec

/ Packaging SPEC.

/ TUBE

Package Type	Units					Dimension		(unit mm ³)

/ Notices