

/ Descriptions

TO-252 NPN Silicon NPN transistor in a TO-252 Plastic Package.


/ Features

High collector-Emitter breakdown voltage, Suitable for transformer, HF Product.


/ Applications

High voltage general purpose applications.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2,4 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}		

/ Electrical Characteristic Curve



/ Package Dimensions




单位：mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.50	0.90	e2	4.43	4.73
b1	0.45	0.55	L1	9.45	9.95
C	0.45	0.55	L2	1.25	1.75
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TO-252

/ Marking Instructions



BR

() /

- 1

150 180

60 90sec;
- 2

245±5

5±0.5sec;
- 3

2 10
- Note:

1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.