



Silicon PNP transistor in a TO-220 Plastic Package.

High DC current gain, High V_{CEO} , High f_T , Complementary pair with MJE15032.

Designed for use as high-frequency drivers in audio amplifiers.



PIN1 Base PIN 2 Collector PIN 3 Emitter


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-250	V
Collector to Emitter Voltage	V_{CEO}	-250	V
Emitter to Base Voltage	V_{EBO}	-5	V
Collector Current - Continuous	I_C	-8	A
Base Current - Continuous	I_B	-2	A
Collector Power Dissipation	P_D	2	W
	$P_D(T_c=25^\circ C)$	50	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-65 ~ 150	
Thermal Resistance, Junction to Case	R_{JC}	2.5	/W
Thermal Resistance, Junction to Ambient	R_{JA}	62.5	/W

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage*	$*V_{CEO}$	$I_C=-10mA$ $I_B=0$	-250			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=-250V$ $I_E=0$			-10	A
Emitter Cut-Off Current	I_{EBO}	$V_{BE}=-5V$ $I_C=0$			-10	A
DC Current Gain	$*h_{FE(1)}$	$V_{CE}=-5V$ $I_C=-1A$	50		200	
	$*h_{FE(2)}$	$V_{CE}=-5V$ $I_C=-0.5A$	70			
	$*h_{FE(3)}$	$V_{CE}=-5V$ $I_C=-2.0A$	10			
Collector to Emitter Saturation Voltage*	$*V_{CE(sat)}$	$I_C=-1A$ $I_B=-0.1A$			-0.5	V
Base to Emitter On Voltage*	$*V_{BE(on)}$	$V_{CE}=-5V$ $I_C=-1A$			-1	V
Transition Frequency	f_T	$V_{CE}=-10V$ $I_C=-500mA$ $f=1MHz$	30			MHz


 μ

 *Pulse Test: Pulse Width 300 μs , Duty Cycle 2%.




单位: mm

TO-220



Symbol	Dimensions in Millimeters		Symbol	Dimensions in Millimeters	
	Min	Max		Min	Max
Δ	0.2	9.8	Δ	0.2	1.4
R	0.25	0.35	R	0.25	0.35
B1	16.1	16.4	B1	16.1	16.4
a	0.5	0.6	a	0.5	0.6
b1	1.22	1.32	b1	1.22	1.32
C	0.2	0.25	C	0.2	0.25
C1	1.25	1.45	C1	1.25	1.45



BR


15033

Note:

BR: Company Code

15033: Product Type.

****: Lot No. Code, code change with Lot No.



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

270 5 10 1 sec. Temp.:270±5 Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 袋	袋 盒	只 盒	盒 箱	只 箱	袋	盒	箱

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱