

/ Descriptions

SOT-23
Silicon Diode in a SOT-23 Plastic Package.


/ Features

Fast Switching, High Conductance. HF Product.


/ Applications

Small signal diode.

/ Equivalent Circuit



/ Pinning



PIN: See Equivalent Circuit.

/ hFE Classifications & Marking

Type	MMBD4148	MMBD4148SE	MMBD4148CC	MMBD4148CA
Marking	H5H	HD4	HD5	HD6

MMBD4148/SE/CC/CA

Rev.H Apr.-2026



蓝箭电子
 BLUE ROCKET ELECTRONICS
DATA SHEET

Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_{RRM}	100	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0S)$	1.0	A
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0\mu S)$	2.0	A
Power Dissipation	PC	350	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	357	/W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_R	$I_R=5.0\mu A$	75			V
		$I_R=100\mu A$	100			V
Forward Voltage	V_F	$I_F=10mA$			1.0	V




/ Electrical Characteristic Curve




/ Package Dimensions


SOT-23

单位: mm





() /



- Note:
- 1

150 180

60 90sec;

2

245±5

5±0.5sec;
- 3

2 10 /sec.
- 1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices