


/ Descriptions


/ Features

/ Applications


/ Equivalent Circuit



/ Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode



/ Marking

/ Absolute Maximum Ratings(Ta=25)


			±	
			±	

/ Electrical Characteristics(Ta=25℃)


[illegible]

[illegible]

/ Electrical Characteristic Curve



/ Package Dimensions



, M y f / Marking Instructions

% â Å - ~ £

KE

^a ¢ y
1 + y ° Z W A
**** y ÿ D Z W A k š ÿ D Z J

Note:
1 + y Product Type Code
**** y Lot No. Code, code change with Lot No

, M y f / Marking Instructions

E â Å - ~ £

AE

^a ¢ y

1 + y ° Z W A

**** y ÿ D Z W A k š Ÿ D Z J


Note:

1 + y Product Type Code

**** y Lot No. Code, code change with Lot No

šWD t... •Žč (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

7HPSHUDWXUH



7LPH VHF

a č y

10• Ä ½ “† 150 ½180 - k ž • 60 ½90sec;

20• Q > “† 245 r5 - k ž • 4 Ò 5 r0.5sec;

30•D N ò i Ò 0 ,† 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“† y 260 r5 -

ž • y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit /Æmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
SMBF	5,000	2	10,000	7	70,000	13 s ×12	336X336X40	380X335X366

„Đ y f / Notices