


Silicon NPN transistor in a TO-92 Plastic Package.

High P_C and I_C .


Medium power amplifier applications.



PIN1 Collector PIN 2 Base PIN 3 Emitter


See Marking Instructions.


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V



T0-92

Unit: mm






Note:

BR: Company Code.

X450: Product Type.

***: Lot No. Code,code change with Lot No.



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

,

Time:60~90sec.
- 2.Peak Temp.:255 5

,

Duration:5 0.5sec.
3. Cooling Speed: 2~10

,

/sec.

270 5

10 1 sec.

Temp:270±5

Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)		
	只 袋	袋 盒	只 盒	盒 箱	只 箱	袋	盒	箱

/ AMMO

Package Type 封装形式	Units 包装数量			Dimension 包装尺寸 (unit: mm3)
	只 纸带	纸带 盒	纸带	